



Model	WINGSTER
Pixel pitch	0.78 mm
Screen diagonal	135 "
Brightness	1,000 nit
Pixel density	3840 x 2160 px; 1,643,655 px/m ²
LED-type	MiP (MicroLED-in-Package), CCT (Common Cathode Technology), Flip chip
Lifespan LED	100,000 hours
Viewing angle	≥ 175° horizontal; ≥ 175° vertical
Refresh Rate	7680 Hz
Scan Rate	1/36
Processing	Novastar
Input signal	2x HDMI2.0 input, digital audio out, airplay, E-share
Power consumption	Max.: 2650 W; 525 W/m ² Average: 883.33 W; 165 W/m ²
Input voltage	100 - 240 V / 50 - 60 Hz
Operating temperature	0 to +40 °C
Humidity operating	10 to 65%
Unit dimensions (WxHxD)	Unfolded and up: 3010 x 424.5 x 760 mm; (= 7.297745 m ³) Unfolded and down: 3010 x 1799.5 x 760 mm Folded and up: 1862 x 2424.5 x 760 mm Folded and down: 1862 x 1799.5 x 796 mm
Unit weight with lifter	255 kg
Unit weight without lifter	130 kg
Maintenance	Front Service
Protection	IP30 (front) / IP30 (back)
Certification	CE, RoHS, EMC class A, TÜV